MANCHESTER, IOWA Mixed-Use SUBDIVISION

Table of Contents C001- COVER SHEET G001- GENERAL COMMENTS CD01- EXISTING CONDITIONS C101- SITE PLAN C301- GRADING PLAN C3O2 - DETENTION A C303 - DETENTION B C304 - DETENTION C C305 - OUTLET DETAILS C201- BIKE PATH C202- LOCAL STREET C203- ARTERIAL STREET C401- IOWA AVF. C402- EMILY AVE. C403-TRAVIS ST. C404- JORDAN DR. C405- JORDAN DR. 2 C406- BRANDON ST.

C407- RICK ST.

C501 - PHASING PLAN





PROJECT LOCATION MAP

THE UNIVERSITY OF IO

CIVIL AND ENVIRONMENTAL ENGINEERS

FROMERING APTS AND SORT

TO S CAPTOR

ONA CITY, FOW S

PHOME 3385,355

PHOME 3385,355

COWA CONTROLLERING

EDUCATIONAL - NOT

Manchester Subdivision

75 BAILEY DR AANCHESTER, IOWA

SHEET NAME

Cover Page

GENERAL CONSTRUCTION NOTES

 TOPOGRAPHICAL INFORMATION BASED UPON LIDAR DATA PROVIDED BY IOWA DEPARTMENT OF NATURAL RESOURCES.

2. THE MATERIAL AND THE CONSTRUCTION OF THIS PROJECT SHALL BE DONE IN CONFORMANCE WITH THE IOWA STATEWIDE URBAN DESIGN AND SPECIFICATIONS (SUDAS) AND THE SPECIFICATIONS PROVIDED IN THIS DRAWING SET

3. LOCATIONS OF UTILITIES SHOWN ON THESE PLANS ARE APPROXIMATE ONLY, CONTRACTOR SHALL BE RESPONSIBLE FOR VERYFHING THE LOCATION OF UTILITIES, PROTECTIONS ALL EXISTING UTILITIES, THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL ON SITE COORDINATION WITH UTILITY COMPANIES AND

PUBLIC AGENCIES AND FOR OBTAINING ALL REQUIRED PERMITS AND PAYING ALL REQUIRED FEES.

4. WHERE AN EXISTING UTILITY IS FOUND TO CONFLICT WITH THE PROPOSED WORK, THE LOCATION, ELEVATION AND SIZE OF THE UTILITY SHALL BE ACCURATELY DETERMINED WITHOUT DELAY BY THE CONTRACTOR AND THE INFORMATION FURNISHED TO THE ENGINEER FOR RESOLUTION OF THE CONFLICT.

5. ANY ALTERATIONS TO THESE DRAWINGS MADE IN THE FIELD DURING CONSTRUCTION SHALL BE RECORDED BY THE GENERAL CONTRACTOR ON "35-RILL" TORANINGS.

6. THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS TO PROTECT HIS EMPLOYEES, AS WELL AS PUBLIC FROM INJURY DURING THE ENTIRE CONSTRUCTION PERIOD USING ALL NECESSARY SAFEQUARDS, INCLUDING BUT NOT LIMITED TO THE ERECTION OF TEMPORARY WALKS, STRUCTURES,

PROTECTIVE BARRIERS, COVERING, OR FENCES AS NEEDED.

7. THE CONTRACTOR SHALL REMOVE ALL SUFFACE VEGETATION PRIOR TO GRADING THE STATE SHALL BE REMOVED BY THE CONTRACTOR. SHALL BE REMOVED BY THE CONTRACTOR SHALL BE INSTALLED BY THE CONTRACTOR. THE CONTRACTOR SHALL BE RESPONSBELE FOR MAINTAINING THESE TEMPORARY EROSION CONTROL MERCAUSES THAT BE INCIDENTAL TO

8. ALL UNSHITBEL UNCONTAMINATED DESESS SOL FROM CONSTRUCTION ACTIVITIES SHALL BE DISPOSED OF BY THE CONTRACTOR AT 100 ADDITIONAL SCISTIO. ACTIVITIES OF THE CONTRACTOR AT 100 ADDITIONAL SCISTIO. ACTIVITIES AND ACTIVITIES OF THE A

9. CONTRACTOR IS RESPONSIBLE FOR STAKING CONSTRUCTION BASELINES IN FIELD BY A PROFESSIONAL SURVEYOR AND APPROVED BY THE ENGINEER.

10. NO FILL SHALL CONTAIN HAZARDOUS MATERIALS.

11. IT IS A CONTRACTOR RESPONSIBILITY TO VISIT THE PROJECT SITE TO VERIFY ALL QUANTITIES AND CONDITIONS PRIOR TO SUBMITTING BID.

12. CONTRACTOR'S STAGING AREA MUST BE WITHIN THE CONTRACT LIMIT LINE AND IN AREAS APPROVED BY OWNER.

13. CONTRACTOR SHALL KEEP ALL STREETS, AND WALKS THAT ARE NOT RESTRICTED FROM THE PUBLIC USE DURING CONSTRUCTION CLEAN AT ALL

14. CONTRACTOR SHALL USE ACCEPTABLE METHODS AND MATERIALS TO MAINTAIN ADEQUATE DUST CONTROL THROUGHOUT CONSTRUCTION. CONTRACTOR SHALL DEWATER AS NEEDED.

15.CONTRACTOR SHALL COORDINATE ALL WORK WITH THE OWNER

EROSION AND SEDIMENT CONTROL

1. ALL SEDIMENT AND EROSION CONTROL DEVICES ALL SEDIMENT AND EROSION CONTROL
 DEVICES SHALL BE PUT INTO PLACE PRIOR TO BEGINNING ANY CONSTRUCTION REFER TO PLAN
 FOR APPROXIMATE LOCATION OF EROSION AND SEDIMENT CONTROL. REFER TO SPECS AND
 DETAIL SERD YEAP OF EROSION AND SEDIMENT CONTROL

2. CONTRACTOR SHALL BE RESPONSIBLE FOR THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CONTINUAL MAINTENANCE OF ALL CONTROL DEVICES DURING THE PROJECT.
3. EXCAVATED MATERIAL STOCKPILED ON THE SITE EXCAVATED MATERIAL STOCKPILED ON THE SITE SHALL BE SURROUNDED BY A RING OF UNBROKEN SEDIMENT AND EROSION CONTROL FENCE. THE LIMITS OF ALL GRADING AND DISTURBANCE SHALL BE KEPT TO A MINIMUM WITHIN THE APPROVED BACE OF CONSTRUCTION. ALL AREAS OUTSIDE OF THE LIMIT OF CONTRACT SHALL REMAIN TOTALLY UNDISTURBED UNLESS OTHERWISE NOTED.
ALL CATCH BASINS AND DRAIN GRATES WITHIN LIMIT ALL CATCH BASINS AND DRAIN GRATES

 ALL CATCH BASINS AND DRAIN GRATES WITHIN LIMIT ALL CATCH BASINS AND DRAIN GRATES WITHIN LIMIT OF CONTRACT SHALL BE PROTECTED WITH FILTER FABRIC DURING THE ENTIRE DURATION OF CONSTRUCTION.

5. EROSION CONTROL BARRIERS TO BE INSTALLED AT EROSION CONTROL BARRIERS TO BE INSTALLED AT THE TOE OF SLOPES.

6. ANY AREA OUTSIDE THE PROJECT LIMIT THAT IS ANY AREA OUTSIDE THE PROJECT LIMIT THAT IS DISTURBED SHALL BE RESTORED TO ITS ORGINAL CONDITION AT NO COST TO THE OWNER. 7. ALL POINTS OF CONSTRUCTION EGRESS OR INGRESS ALL POINTS OF CONSTRUCTION EGRES OR INCRESS SHALL BE MAINTAINED TO PREPURITY TRACKING OR INOWING OF SEPIMENT ON THE THE UNIVERSITY OF IOWA

"IL AND ENVIRONMENTAL ENGINEERING DATE:

AND SAMANS CANDER FOR THE ENGINEERING TO THE ENGINEERING TO THE ENGINEERING TO SERVE A COMPANY OF THE ENGINEERING THE ENVIRONMENT OF THE E

Ë

IOWA

ONL & ENDOMENTAL
ENGINEERING

EDUCATIONAL - NOT FOR CONSTRUCTION

FOR CONSTRUCTION


Manchester Subdivision
278 Bailey Dr.
Marchester Iwas

SHEET NAME

General Notes


HEET NO.

G001





THE FOLLOWING SHOWS THE DIMENSIONS FOR THE BIKE DESIGN. THE 14' COORIDOR CONTAINS A 10' MAIN BIKE WITH 2' OF CLEARANCE ON EACH SIDE OF THE TRAIL. THE PCC PAVEMENT IS 6" THICK AND IS A 1.5% CROSS SLOPE, AS RECOMMENDED BY IOWA'S STATEWIDE URBAN DESIGN AND SPECIFICATIONS.



CEE: 4850 12/11/2020

THE UNIVERSITY OF IOWA CIVIL AND ENVIRONMENTAL ENGINEERING




EDUCATIONAL - NOT FOR CONSTRUCTION

Manchester Subdivision

275 Bailey Dr. Manchester, Iowa

SHEET NAME

Bike Path



ERAL NOTES

nen utilities are in the right-of-way, the following should be adhered to unless otherwise approved by the Jurisdiction:

Sanitary sewer: under pavement should be installed in the center of the street, per design:

Storm Sewers: The normal location is 1.5 feet from the back of curb. In areas of combination manholes and intakes are used, the location increases to 5 feet.

Vater Mains, Valves, and Hydrants:

The normal location is 5 feet behind the back of curb.

For local streets and minor collectors with limited right-of-way, use a 90 degrees anchoring Tee fitting between the hydrant main

Depth of Bury: Public Utilities

ter: 5 feet. Refer to Chapter 4 in SUDAS

itary Sewer: minimum 12 feet.

Maintain a minimum separation of 1 feet from the edge of the sidewalk or red use path to obstructions such as five hydrants.utility poles, signs, etc.

Meet object setback, clear zone, and curb offset requirements of Section 5C-1.

Pipe Bedding and Backfill:

Class III and Class IVA Backfill Material: Class III and Class IVA Backfill Material:

Compact to at least 95% of Standard Proctor Density within right-of-way. Compact to at least 95% of Standard Proctor Density within right-of-way.

Compact to at least 90% of Standard Proctor Density outside right-of-way. Compact to at least 90% of Standard Proctor Density outside right-of-way. Obtain required compaction within a soil moisture range of optimum moisture obtain required compaction within a soil moisture range of optimum moisture to 4% above optimum moisture c Per SUDAS

Jointing L-1 dowels

'C" Joints


)avliahtina

Should be a 50:1 slope on either side to account for from yards

THE UNIVERSITY OF IOWA CIVIL AND ENVIRONMENTAL ENGINEERING

Manchester Subdivision

SHEET NAME Local Street



GENERAL NOTES

A.When utilities are in the right-of-way, the following should be adhered to unless otherwise approved by the Jurisdiction:

1. Sanitary sewer: under pavement should be installed in the center of the street, per design :

B.Storm Sewers: The normal location is 1.5 feet from the back of curb. In greas of combination manholes and intakes are used the location increases to 5 feet.

C.Water Mains, Valves, and Hydrants:

1. The normal location is 5 feet behind the back of curb.

2. For local streets and minor collectors with limited right-of-way, use a 90 degrees anchoring Tee fitting between the hydrant main

B. Depth of Bury

1. Public Utilities:

Water: 5 feet. Refer to Chapter 4 in SUDAS

Sanitary Sewer: minimum 12 feet.

C. Maintain a minimum separation of 1 feet from the edge of the sidewalk or shared use path to obstructions such as five hydrants, utility poles, signs, etc.

D..Meet object setback, clear zone, and curb offset requirements of Section 5C-1.

E..Pipe Bedding and Backfill:

Class III and Class IVA Backfill Material: Class III and Class IVA Backfill Material:

Compact to at least 95% of Standard Proctor Density within right-of-way. Compact to at least 95% of Standard Proctor Density within right-of-way.

Compact to at least 90% of Standard Proctor Density outside right-of-way. Compact to at least 90% of Standard Proctor Density outside right-of-way.

Obtain required compaction within a soil moisture range of optimum moisture Obtain required compaction within a soil moisture to 4% above optimum moisture c Per SUDAS

Jointing L-2 dowels

'C" Joints

Should be a 50:1 slope on either side to account for from yards

EDUCATIONAL NOT

12/11/2020 E.


THE UNIVERSITY OF IOWA


CIVIL AND ENVIRONMENTAL ENGINEERING

Manchester Subdivision

Bailey

SHEET NAME Arterial Street





DETENTION BASIN A SEE DETAIL 1 ON C305 FOR OUTLET DETAILS



DETENTION BASIN A


CEE: 4850 12/11/2020 THE UNIVERSITY OF 10WA CIVIL AND ENVIRONMENTAL ENGINEERING

EDUCATIONAL - NOT FOR CONSTRUCTION MANCHESTER SUBDIVISION

275 BAILEY DR. MANCHESTER, IOWA

SHEET NAME BASIN A





DETENTION BASIN B

FOLECT: CCE: 4850
NATE: 12/11/2020
RAMN BY: TSW

THE UNIVERSITY OF ION

CIVIL AND ENVIRONMENTAL ENGINEERIN

405 SEAMAS CENTER FOR 1

ENGINEERINE ARTS AND SCENCE

103 S CAPTION


103 S CAPTION

E logo 6W - noText.tif


MANCHESTER SUBDIVISION
Z76 BAILEY DR.

SHEET NAME BASIN B

SHEET NO.



DETENTION BASIN C SEE DETAIL 3 ON C305 FOR OUTLET INFORMATION




DETENTION BASIN C v:1"=5" H:1"=20"


CEE: 4850 12/11/2020


EDUCATIONAL - NOT FOR CONSTRUCTION

MANCHESTER SUBDIVISION

SHEET NAME BASIN C







DWN ARE IN FEET C305

CEE: 4850 12/11/2020

PROJECT: DATE:

THE UNIVERSITY OF 10WA CIVIL AND ENVIRONMENTAL ENGINEERING


EDUCATIONAL - NOT FOR CONSTRUCTION


MANCHESTER SUBDIVISION


SHEET NAME BASIN C


275 BAILEY DR. MANCHESTER, IOWA


ALL DIMENSIONS SHOWN ARE IN FEET












0+00 1+00 2+00 3+00 4+00 5+00 6+00 7+00 8+00 9+00 10+00 11+00 12+00 13+00 14+00 15+00 16+00 17+00



1+00 2+00

